Chromebook 3110

Setup and Specifications



Notes, cautions, and warnings

(i) NOTE: A NOTE indicates important information that helps you make better use of your product.

CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

MARNING: A WARNING indicates a potential for property damage, personal injury, or death.

© 2022 Dell Inc. or its subsidiaries. All rights reserved. Dell, EMC, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

Contents

Chapter 1: Views of Chromebook 3110	4
Right	
Left	4
Тор	5
Front	6
Bottom	6
Service Tag	7
Battery charge and status light	7
Chapter 2: Specifications of Chromebook 3110	8
Dimensions and weight	8
Processor	8
Chipset	9
Operating system	9
Memory	9
External ports	9
Internal slots	10
Wireless module	10
WWAN module (optional)	11
Audio	11
Storage	11
Keyboard	12
Camera	12
Touchpad	13
Power adapter	13
Battery	14
Display	14
GPU—Integrated	15
Hardware security	16
Operating and storage environment	16
Chapter 3: Keyboard shortcuts of Chromebook 3110	17
Chapter 4: Getting help and contacting Dell	18

Views of Chromebook 3110

Right



1. One wedge-shaped lock slot

With HDMI 1.4b port



- 1. One USB 3.2 Gen 1 port with PowerShare
- 2. One wedge-shaped lock slot

Left



- 1. LED status light
- 2. One USB 3.2 Gen 1 Type-C port with Power Delivery and DisplayPort Alt mode
- 3. One USB 3.2 Gen 1 port with PowerShare
- 4. One headset (headphone and microphone combo) port

With HDMI 1.4b port




- 1. LED status light
- 2. One USB 3.2 Gen 1 Type-C port with Power Delivery and DisplayPort Alt mode
- 3. One HDMI 1.4b port (optional)
- 4. One headset (headphone and microphone combo) port

Top




- 1. Power button
- 2. Keyboard
- 3. Touchpad

Front



- 1. Left microphone (optional)
- 2. Camera
- **3.** Camera status LED
- 4. Right microphone
- 5. Display panel

Bottom



1. Service tag location

- 2. Base cover
- 3. Speakers

Service Tag

The service tag is a unique alphanumeric identifier that allows Dell service technicians to identify the hardware components in your computer and access warranty information.



Battery charge and status light

The following table lists the battery charge and status light behavior of your Chromebook 3110.

Table 1. Battery charge and status light behavior

Power Source	LED Behavior	System Power State	Battery Charge Level
AC Adapter	Solid Amber	S0 - S5	< Fully Charged
AC Adapter	Solid White	S0 - S5	Fully Charged
Battery	Solid White	S0 - S5	Adequately Charged
Battery	Blinking Amber (1 sec. on & 1 sec. off)	S0 - S5	battery is critically low (< 10%)

- S0 (ON) System is turned on.
- S5 (OFF) The system is in a shutdown state.

Specifications of Chromebook 3110

Dimensions and weight

The following table lists the height, width, depth, and weight of your Chromebook $3110\,$.

Table 2. Dimensions and weight

Description	Values
Height:	
Front height	20.75 mm (0.817 inches)
Rear height	20.75 mm (0.817 inches)
Width	303.9 mm (11.96 inches)
Depth	207.9 mm (8.19 inches)
Weight i NOTE: The weight of your computer depends on the configuration ordered and manufacturing variability.	1.28 kg (2.83 lbs)

Processor

The following table lists the details of the processors supported by your Chromebook 3110.

Table 3. Processor

Description	Values
Processor type	Intel Celeron N4500
Processor wattage	6 W
Processor core count	2
Processor thread count	2
Processor speed	Up to 2.8 GHz
Processor cache	4 MB
Integrated graphics	Intel UHD graphics

Chipset

The following table lists the details of the chipset supported by your Chromebook 3110.

Table 4. Chipset

Description	Values
Chipset	Intel Celeron N4500
Processor	Intel Celeron N4500
DRAM bus width	64-bit
Flash EPROM	16 MB
PCle bus	Up to Gen3

Operating system

Your Chromebook 3110 supports the following operating systems:

Google Chrome operating system

Memory

The following table lists the memory specifications of your Chromebook $3110\,$.

Table 5. Memory specifications

Description	Values
Memory slots	On-board i NOTE: Memory is on-board and cannot be upgraded.
Memory type	LPDDR4x
Memory speed	2933 MHz, non-ECC
Maximum memory configuration	8 GB
Minimum memory configuration	4 GB
Memory size per slot	N/A
Memory configurations supported	 4 GB, 2 x 2 GB, LPDDR4x, 2933 MHz, single-channel 8 GB, 4 x 2 GB, LPDDR4x, 2933 MHz, dual-channel

External ports

The following table lists the external ports on your Chromebook 3110 .

Table 6. External ports

Description	Values
USB ports	One USB 3.2 Gen 1 port with PowerShare

Table 6. External ports (continued)

Description	Values
	One USB 3.2 Gen 1 Type-C port with DisplayPort Alt mode
Audio port	One headset (headphone and microphone combo) port
Video port/ports	 One HDMI 1.4b port (optional) One USB 3.2 Gen 1 Type-C port with Power Delivery and DisplayPort Alt mode
Media-card reader	Not supported
Power-adapter port	65 W, USB Type-C i NOTE: Adapter is over USB 3.2 Gen 1 Type-C with DisplayPort Alt mode
Security-cable slot	One wedge-shaped lock slot

Internal slots

The following table lists the internal slots of your Chromebook $3110\,$.

Table 7. Internal slots

Description	Values
M.2	One M.2 3042 slot for WWAN module (optional)
	NOTE: To learn more about the features of different types of M.2 cards, see the knowledge base article 000144170 at www.dell.com/support.

Wireless module

The following table lists the Wireless Local Area Network (WLAN) module supported on your Chromebook 3110.

Table 8. Wireless module specifications

Description	Values
Model number	Intel AX201
Transfer rate	Up to 2400 Mbps
Frequency bands supported	2.4 GHz/5 GHz
Wireless standards	 WiFi 802.11a/b/g Wi-Fi 4 (WiFi 802.11n) Wi-Fi 5 (WiFi 802.11ac) Wi-Fi 6 (WiFi 802.11ax)
Encryption	64-bit/128-bit WEP AES-CCMP TKIP
Bluetooth	Bluetooth 5.2

WWAN module (optional)

The following table lists the Wireless Wide Area Network (WWAN) module supported on your Chromebook 3110.

Table 9. WWAN module specifications

Description	Values
Model number	Intel XMM 7360 Global LTE-Advanced, CAT 9
Transfer rate	Up to 450 Mbps DL/50 Mbps UL (Cat 9)
Frequency bands supported (1,2,3,4,5,7,8,11,12,13,17,18,19,20,21,26,28,29,30,38,39,40), HSPA+ (1, 2, 4,5, 8)	
NOTE: For instructions on how to find your computer's IMEL (International Mobile Station Equipment Identity) number	

NOTE: For instructions on how to find your computer's IMEI (International Mobile Station Equipment Identity) number, see the knowledge base article 000143678 at www.dell.com/support.

Audio

The following table lists the audio specifications of your Chromebook 3110.

Table 10. Audio specifications

Description		Values
Audio controller		Dialog DA7219 or Cirrus Logic CS42L42
Stereo conversion		Supported
Internal audio interface	9	I2S
External audio interfac	е	Headset (headphone and microphone combo) port
Number of speakers		Two
Internal-speaker amplif	fier	Maxim MAX98360
External volume contro	ols	Keyboard shortcut controls
Speaker output:		
	Average speaker output	2 W
	Peak speaker output	2.5 W
Subwoofer output		Not Supported
Microphone		Single digital microphone or Dual digital microphones (optional)

Storage

This section lists the storage options on your Chromebook 3110.

Your Chromebook 3110 supports one of the following storage configurations:

• One 32 GB eMMC, on-board

- One 64 GB eMMC, on-board
- i NOTE: Storage is on-board and cannot be upgraded.

Table 11. Storage specifications

Storage type	Interface type	Capacity
eMMC for Celeron processors	On-board	Up to 64 GB

Keyboard

The following table lists the keyboard specifications of your Chromebook $3110\ .$

Table 12. Keyboard specifications

Description	Values	
Keyboard type	Standard non-backlit keyboard without numpad	
Keyboard layout	QWERTY	
Number of keys	 United States and Canada: United States and Canada: 74 keys keys United Kingdom: United Kingdom: 75 keys keys Japan: Japan: 78 keys keys 	
Keyboard size	X=19.05 mm key pitch Y=18.05 mm key pitch	
Keyboard shortcuts	Y=18.05 mm key pitch Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character press Shift and the desired key. To perform secondary functions, press Fn and the desired key. (i) NOTE: You can define the primary behavior of the function keys (F1–F12) changing Function Key Behavior in BIOS setup program.	

Camera

The following table lists the camera specifications of your Chromebook $3110\,$.

Table 13. Camera specifications

Des	cription	One	Two
Nun	nber of cameras	One	One
Can	nera type	RGB HD camera, single-integrated microphone	RGB HD camera dual- array microphones
Can	nera location	Front camera	Front camera
Can	nera sensor type	CMOS sensor technology	CMOS sensor technology
Can	nera resolution (RGB):		
	Still image	0.92 megapixel	0.92 megapixel

Table 13. Camera specifications (continued)

Des	cription	One	Two
	Video	1280 x 720 (HD) at 30 fps	1280 x 720 (HD) at 30 fps
Diag	gonal viewing angle:	78.6 degrees	78.6 degrees

Touchpad

The following table lists the touchpad specifications of your Chromebook $3110\,$.

Table 14. Touchpad specifications

Description	Values
Touchpad resolution:	
Horizontal	>300 dpi
Vertical	N/A
Touchpad dimensions:	
Horizontal	99.40 mm (3.91 in.)
Vertical	59.40 mm (2.34 in.)
Touchpad gestures	For more information about touchpad gestures available on Windows, see the Microsoft knowledge base article 4027871 at support.microsoft.com.

Power adapter

The following table lists the power adapter specifications of your Chromebook $3110\,$.

Table 15. Power adapter specifications

Descrip	otion	Values
Туре		Pecos 65 W AC adapter, USB-C
Input vo	oltage	100 VAC-240 VAC
Input fr	equency	50 Hz-60 Hz
Input cu	ırrent (maximum)	1.70 A
Output	current (continuous)	20 V/3.25 A; 15 V/3 A; 9 V/3 A; 5 V/3 A
Rated o	utput voltage	20VDC/15VDC/9VDC/5VDC
Temper	ature range:	
	Operating	0°C to 40°C (32°F to 104°F)
	Storage	-40°C to 70°C (-40°F to 158°F)

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.

Battery

The following table lists the battery specifications of your Chromebook 3110 .

Table 16. Battery specifications

Description		Option one
Battery type		3-cell, 42 Whr, "smart" lithium-ion
Battery voltage		11.40 VDC
Battery weight (maximum)		0.20 kg (0.44 lb)
Battery dimensions:		<u>'</u>
	Height	191.85 mm (7.55 in.)
	Width	103.25 mm (4.06 in.)
Depth		5.90 mm (0.23 in.)
Temperature range:		
	Operating	0°C to 35°C (32°F to 95°F)
	Storage	-20°C to 65°C (-4°F to 149°F)
Battery operating time		Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.
Battery charging time (approximate)		Standard mode • 0~15 degrees: 4 hours • 16~60 degrees: 3 hours • 46~60 degrees: 3 hours
Coin-cell battery		Not supported
		,

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.

CAUTION: Dell recommends that you charge the battery regularly for optimal power consumption. If your battery charge is completely depleted, connect the power adapter, turn on your computer, and then restart your computer to reduce the power consumption.

Display

The following table lists the display specifications of your Chromebook 3110 .

Table 17. Display specifications

Description	Option one	Option two
Display type	11.6-inch, High Definition (HD), non- touch	11.6-inch, High Definition (HD), touch
Display-panel technology	TN	TN
Display-panel dimensions (active area):		

Table 17. Display specifications (continued)

Description	Option one	Option two
Height	144 mm (5.67 in.)	144 mm (5.67 in.)
Width	256.13 mm (10.08 in.)	256.13 mm (10.08 in.)
Diagonal	294.64 mm (11.60 in.)	294.64 mm (11.60 in.)
Display-panel native resolution	1366 x 768	1366 x 768
Luminance (typical)	220 nits	220 nits
Megapixels	1,049,088	1,049,088
Color gamut	45% NTSC	45% NTSC
Pixels Per Inch (PPI)	135	135
Contrast ratio (min.)	600:1 typ.	500:1 typ.
Response time (max.)	20 ms	16 ms
Refresh rate	60 Hz	60 Hz
Horizontal view angle	+40/-40 degrees	+40/-40 degrees
Vertical view angle	+10/-30 degrees	+10/-30 degrees
Pixel pitch	0.1875 x 0.1875 mm	0.1875 x 0.1875 mm
Power consumption (maximum)	2.80 W	3 W
Anti-glare vs glossy finish	Glossy/Anti-glare	Anti-glare
Touch options	No	Yes
Stylus	No	No

GPU—Integrated

The following table lists the specifications of the integrated Graphics Processing Unit (GPU) supported by your Chromebook 3110 .

Table 18. GPU—Integrated

Controller	External display support	Memory size	Processor
Intel UHD graphics	 One HDMI 1.4b port (optional) One DisplayPort Alt mode over USB 3.2 Gen 1 Type- C port with Power delivery 	Shared system memory	Intel Celeron N4500

Hardware security

The following table lists the hardware security of your Chromebook 3110 .

Table 19. Hardware security

Hardware	e security
H1 Security	ry Chip
One wedge	e-shaped lock slot

Operating and storage environment

This table lists the operating and storage specifications of your Chromebook $3110\,$.

Airborne contaminant level: G1 as defined by ISA-S71.04-1985

Table 20. Computer environment

Description	Operating	Storage
Temperature range	0°C to 35°C (32°F to 95°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS
Shock (maximum)	110 G†	160 G†
Altitude range	-15.2 m to 3048 m (-49.87 ft to 10000 ft)	-15.2 m to 10668 m (-49.87 ft to 35000 ft)

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.

^{*} Measured using a random vibration spectrum that simulates user environment.

[†] Measured using a 2 ms half-sine pulse.

Keyboard shortcuts of Chromebook 3110

Table 21. List of keyboard shortcuts

Function key	Primary behavior
F1	Browser back
F2	Browser refresh
F3	Full screen
F4	Window Overview
F5	Screenshot
F6	Dim Screen
F7	Brighten screen
F8	Mute
F9	Volume down
F10	Volume up
F13	Power key
Alt + search key	Caps lock on temporarily

For information on keyboard shortcuts, see Chromebook keyboard shortcuts.

Getting help and contacting Dell

Self-help resources

You can get information and help on Dell products and services using these self-help resources:

Table 22. Self-help resources

Self-help resources	Resource location
Information about Dell products and services	www.dell.com
Tips	*
Online help for operating system	For support on your Chromebook, refer Chrome OS Support.
Access top solutions, diagnostics, drivers and downloads, and learn more about your computer through videos, manuals and documents.	Your Dell computer is uniquely identified by a Service Tag or Express Service Code. To view relevant support resources for your Dell computer, enter the Service Tag or Express Service Code at www.dell.com/support. For more information on how to find the Service Tag for your computer, see Locate the Service Tag on your computer.
Dell knowledge base articles for a variety of computer concerns	 Go to www.dell.com/support. On the menu bar at the top of the Support page, select Support > Knowledge Base. In the Search field on the Knowledge Base page, type the keyword, topic, or model number, and then click or tap the search icon to view the related articles.

Contacting Dell

To contact Dell for sales, technical support, or customer service issues, see www.dell.com/contactdell.

- (i) NOTE: Availability varies by country/region and product, and some services may not be available in your country/region.
- NOTE: If you do not have an active Internet connection, you can find contact information about your purchase invoice, packing slip, bill, or Dell product catalog.